

# POSi-TECH

## 3 Strand Twisted Polypropylene Rope

**New!**



A strong lightweight general purpose monofilament rope with many uses. It is waterproof, rot and mildew resistant. An excellent insulator. Used by utilities companies for low dielectric loss; may be used with safety around "hot" wires. Low flammability. Will burn but very slowly. Not recommended for use on bits and capstans where heat is a factor because it will tend to stick and fuse. Knot holding: resists bending and flexing, continued wear causes roughness and increased knot-holding properties. For most rope requirements, it is the most economical rope to buy. This synthetic rope is easier to handle than rope made from natural fibers. Highly visible bright yellow makes this rope an excellent choice for roping off areas on construction sites. Not for power cable pulling. Easy to splice.

PART NUMBER	DIAMETER INCHES	LENGTH		LB. PER ROLL	CUBE PER ROLL	BREAK STRENGTH	WORKING LOAD
		Feet	Meter				
ROPL-1410	1/4"	100'	30	1.2	.079	1,238	154
ROPL-1425	1/4"	250'	76	2.99	.23	1,238	154
ROPL-1460	1/4"	600'	183	7.18	.56	1,238	154
ROPL-1412	1/4"	1200'	366	14.4	.76	1,238	154
ROPL-3810	3/8"	100'	30	2.8	.138	2,673	334
ROPL-3825	3/8"	250'	76	7	.345	2,673	334
ROPL-3860	3/8"	600'	183	16.8	.76	2,673	334
ROPL-3812	3/8"	1200'	366	33.6	1.27	2,673	334
ROPL-1210	1/2"	100'	30	4.703	.255	4,158	520
ROPL-1225	1/2"	250'	76	11.75	.638	4,158	520
ROPL-1260	1/2"	600'	183	28.21	1.27	4,158	520
ROPL-1212	1/2"	1200'	366	56.4	3.03	4,158	520

## Conduit Measuring Tape

**New!**



Eliminate wasted wire cuts, pre-measure your cable run with Posi-tech Conduit Measuring Tape. Waterproof polyester construction. Foot measurements printed every foot from 0 to 3,000 feet.

PART NUMBER	WIDTH	LENGTH		LB. PER ROLL	CUBE PER ROLL	BREAK STRENGTH
		Feet	Meter			
ROCM-3630	3/16"	3,000	914	3.4	.255	130 LBS.

# POSI-TECH

## Wire Pulling Twine in a Bucket



Polypropylene provides high strength and is lightweight. This synthetic material provides low elasticity and good electrical resistance. Used to pull rope through conduit, this monofilament blue spiral wrap twine resists tangling when being dispensed. Although this twine is not for pulling wire or cable, its rot and mildew resistance make it a good choice for use with power fishing systems. Available in a reusable plastic bucket with handle and center pull for easy dispensing. Guaranteed break strength.

PART NUMBER	DIAMETER INCHES	LENGTH		LB. PER ROLL	CUBE PER ROLL	BREAK STRENGTH
		Feet	Meter			
ROPL-6501	1/8"	5,200	1,585	10	.67	240

## Nylon Seine Twine - Fish Line (Center Pull)



This twine made of 100% filament nylon is strong, lightweight, and nearly indestructible. Excellent for tying, it resists mildew, rot, abrasion, oil, grease, and most chemicals. Can be pulled with wire for the ability to add wires later.

**New!**

PART NUMBER	SIZE	LENGTH		CUBE PER ROLL	BREAK STRENGTH	CASE PACK
		Feet	Meter			
RONT-2150	9	2,150	655	.037	98 lbs.	12